

**- Gel type HEPA filter**



Specifications	
Efficiency	H13, H14 EN:1822
Filter media	Glassfiber
Frame	Aluminum alloy
Seal	Polyurethane
Gasket	Fluid gel seal
Size	Standard & customized
Humidity	80%
MAX temp	80°C
Final pressure drop	600Pa
Construction	Panel, Flanged
Faceguard	Optional

**-Parameters**

Size	Airflow rate	Efficiency / Pressure drop	Efficiency / Pressure drop
305*305*80mm (Panel)	250m <sup>3</sup> /h	H13 / 220Pa	H14 / 230Pa
305*610*80mm (Panel)	500m <sup>3</sup> /h	H13 / 220Pa	H14 / 230Pa
610*610*80mm (Panel)	1000m <sup>3</sup> /h	H13 / 220Pa	H14 / 230Pa
610*762*80mm (Panel)	1250m <sup>3</sup> /h	H13 / 220Pa	H14 / 230Pa
610*915*80mm (Panel)	1500m <sup>3</sup> /h	H13 / 220Pa	H14 / 230Pa
610*1220*80mm (Panel)	2000m <sup>3</sup> /h	H13 / 220Pa	H14 / 230Pa
305*305*95mm (Panel)	500m <sup>3</sup> /h	H13 / 200Pa	H14 / 210Pa
305*610*95mm (Panel)	1000m <sup>3</sup> /h	H13 / 200Pa	H14 / 210Pa
610*610*95mm (Panel)	2000m <sup>3</sup> /h	H13 / 200Pa	H14 / 210Pa
610*762*95mm (Panel)	2500m <sup>3</sup> /h	H13 / 200Pa	H14 / 210Pa
610*915*95mm (Panel)	3000m <sup>3</sup> /h	H13 / 200Pa	H14 / 210Pa
610*1220*95mm (Panel)	4000m <sup>3</sup> /h	H13 / 200Pa	H14 / 210Pa

\* For both standard and customized sizes, efficiency available

## -Constructions



Panel design



Flange design

## -Details



**CHANGSHA EAWAYFILTER EQUIPMENT CO.,LTD**

Website: [www.cleanroom-ffu.com](http://www.cleanroom-ffu.com)

Email: [sales@cleanroom-ffu.com](mailto:sales@cleanroom-ffu.com)

Mob: 0086-13631590514

Whatsapp: 0086-13631590514

Add: 9th Building, Jianshan Road, Changsha, Hunan, China