

**- 95 DOP air filter**



Specifications	
Efficiency	H11 95%
Filter media	Glassfiber
Frame	SUS, Gal, Wooden
Seal	AB Component polyurethane
Gasket	EVA
Size	Standard & customized
Humidity	80%
MAX temp	80°C
Final pressure drop	450Pa
Construction	DTF, Boxed, Flanged
Faceguard	Optional (Metal mesh)

**- Parameters**

ITEM NO	Size (mm)	Efficiency	Filter area(m2)	Airflow rate (m3/h)	Pressure drop (Pa)
DH33292-H11	305x305x292	H11	6	500	150
DH36292-H11	305x610x292	H11	12	1000	150
DH46292-H11	457x610x292	H11	18	1500	150
DH66292-H11	610x610x292	H11	24	2000	150
DH67292-H11	610x762x292	H11	30	2500	150
DH25292-H11	287x595x292	H11	11	900	150
DH55292-H11	595x595x292	H11	22	1850	150
DH33220-H11	305x305x220	H11	4.5	375	150
DH36220-H11	305x610x220	H11	9	570	150
DH46220-H11	457x610x220	H11	14	1130	150
DH66220-H11	610x610x220	H11	18	1500	150
DH67220-H11	610x762x220	H11	22	1880	150
DH25220-H11	287x595x220	H11	8	678	150
DH55220-H11	595x595x220	H11	16	1400	150

DH33150-H11	305x305x150	H11	3	250	150
DH36150-H11	305x610x150	H11	6	500	150
DH46150-H11	457x610x150	H11	9	770	150
DH66150-H11	610x610x150	H11	12	1000	150
DH67150-H11	610x762x150	H11	15	1280	150
DH25150-H11	287x595x150	H11	5.6	460	150
DH55150-H11	595x595x150	H11	11	950	150

\* For both standard and customized sizes, efficiency available